

## WATER WELL PUMPS - 4" Submersible Pumps



# EFSUB5-102-1

## 4" Submersible Pump, 2-Wire

### 1/2 HP - 10 GPM

#### APPLICATIONS

- Provides Smooth Water Passages for Maximum Efficiency

#### FEATURES

- 1-1/4" FNPT Discharge Connection, includes Built-in Check Valve
- Stainless Steel Pump Shaft is Precision Ground for Exact Bearing Fit and Straightness
- Precision Molded Impellers and Diffusers
- Stainless Steel Pump Housing for Maximum Protection Against Corrosion
- Stainless Steel Splined Shaft
- Self-healing Resin System
- Hermetically-sealed Windings
- Filter Check Valve
- Kingsbury-type Thrust Bearing
- Pressure Equalizing Diaphragm
- Removable Water-bloc Lead Connector
- NEMA Mounting Dimensions

#### SPECIFICATIONS

UPC	WARRANTY	WEIGHT	DIMENSIONS (L x D)	PALLET QUANTITY
856594003701	3 Year	23.8 Lbs.	23.4" x 3.5"	50



#### PERFORMANCE CHART

MODEL	HP	GPM	VOLT	GALLONS PER MINUTE PUMPED AT DIFFERENT DEPTHS TO WATER										
				20	40	60	80	100	150	200	250	300	350	400
EFSUB5-102-1	1/2	10	115	-	-	11	9.8	8.7	-	-	-	-	-	-

PERFORMANCE SHOWN IN GPM AT 40 PSI DISCHARGE PRESSURE

### ECO-FLO PRODUCTS

1899 Cottage Street, Ashland, Ohio 44805 • Customer Service: 1-877 326-3561 • Fax: 1-877 326-1994 • [www.ecofloproducts.com](http://www.ecofloproducts.com)