

## WATER WELL PUMPS - 4" Submersible Pumps



# EFSUB5-103

## 4" Submersible Pump, 3-Wire

### 1/2 HP - 10 GPM

#### APPLICATIONS

- Provides Smooth Water Passages for Maximum Efficiency

#### FEATURES

- 1-1/4" FNPT Discharge Connection, includes Built-in Check Valve,
- Stainless Steel Pump Shaft is Precision Ground for Exact Bearing Fit and Straightness
- Precision Molded Impellers and Diffusers
- Stainless Steel Pump Housing for Maximum Protection Against Corrosion
- Stainless Steel Splined Shaft
- Self-healing Resin System
- Hermetically-sealed Windings
- Filter Check Valve
- Kingsbury-type Thrust Bearing
- Pressure Equalizing Diaphragm
- Removable Water-bloc Lead Connector
- NEMA Mounting Dimensions

#### SPECIFICATIONS

| UPC          | WARRANTY | WEIGHT    | DIMENSIONS (L x W x H) | PALLET QUANTITY |
|--------------|----------|-----------|------------------------|-----------------|
| 856594003725 | 3 Year   | 23.6 Lbs. | 22.1" x 3.5"           | 50              |



#### PERFORMANCE CHART

| MODEL      | HP  | GPM | VOLT | GALLONS PER MINUTE PUMPED AT DIFFERENT DEPTHS TO WATER |    |    |     |     |     |     |     |     |     |     |
|------------|-----|-----|------|--|----|----|-----|-----|-----|-----|-----|-----|-----|-----|
|            |     |     |      | 20   | 40 | 60 | 80  | 100 | 150 | 200 | 250 | 300 | 350 | 400 |
| EFSUB5-103 | 1/2 | 10  | 230  | -  | -  | 11 | 9.8 | 8.7 | -   | -   | -   | -   | -   | -   |

PERFORMANCE SHOWN IN GPM AT 40 PSI DISCHARGE PRESSURE

### ECO-FLO PRODUCTS

1899 Cottage Street, Ashland, Ohio 44805 • Customer Service: 1-877 326-3561 • Fax: 1-877 326-1994 • [www.ecofloproducts.com](http://www.ecofloproducts.com)